

Signet 9900 Transmitter



Benefits

The 9900 Transmitter offers “at-a-glance” visibility, easy set-up and the flexibility to combine it with different sensor types.

As a member of the Signet SmartPro® family of instruments, the Signet 9900 Transmitter provides a single channel interface for many different sensor types including Flow, pH/ORP, Conductivity/Resistivity, Salinity, Temperature, Pressure, Level, Dissolved Oxygen and other sensors that output a 4 to 20 mA signal. Each release of the 9900 Transmitter has included new features and capabilities in addition to the already extensive list of capabilities.



Relay Module

Direct Conductivity/
Resistivity Module

H COMM Module

Batch Module

4 to 20 mA
Output Module

Modbus Module

Note: Refer to the 9900 Transmitter manual for modules supported in each generation of the 9900 Transmitters

At-a-glance visibility

The extra-large (3.90" x 3.90") auto-sensing back-lit display with its large characters clearly showing the primary measurement values which can be viewed at 4-5 times the distance over traditional transmitters, even in dark rooms or conditions. The 9900 with its dual line display, shows both Primary and Secondary measurement values and also comes with a separate programmable dial-type digital bar to assist in a quick visual of the applications process.

Quick and easy installation

The intuitive menu system is consistent with GF Signet legacy product ProcessPro® and ProPoint® family of transmitters. The ¼" DIN package allows populating a control panel while reducing overcrowding. All wiring to the 9900 is installed in an easy to remove terminal to assist wiring in crowded conditions.

The 9900 will recognize GF sensors that are wired to the input terminals and assist the operator to quickly modify key parameters in the menu which are specifically required for that particular installation.


With our 0252 Configuration Tool, you can easily set-up the 9900 parameters on your laptop, clone transmitters for specific applications and save the information to a file on your laptop for future programming or to program replacement transmitters.

Flexibility

The 9900 offers complete flexibility, plug-in modules allow the unit to easily adapt to meet changing customer needs.

Optional modules include the Modbus, Relay, Direct Conductivity/Resistivity, H COMM, Batch and 4 to 20 mA Output.

The unit can be used with default values for quick and easy programming or can be customized with labeling, adjustable minimum and maximum dial settings, and unit of measure and decimal location choices.



Relay Module

- Adds two programmable dry-contact relays
- Hysteresis and time delay available for each relay
- Depending on the sensor type, there are a total of 23 Relay modes available

4 to 20 mA Output Module

- Adds one extra 4 to 20 mA output
- Output can be used for primary or secondary measurement
- Settings are independent from 4 to 20 mA output in base unit

Direct Conductivity/Resistivity Module

- Interfaces Conductivity/Resistivity and Salinity Electrodes directly to the 9900 Transmitter
- Conductivity/Resistivity and Salinity Measurements may also be performed via the 2850 Sensor Electronics through the 9900 (S³L) input

Batch Module

- Adds Batch capability to the 9900 Transmitter (Generation II or later)
- Compatible with all Signet flow sensors
- Up to 10 batch sizes can be stored in one 9900 with customized names and K-Factors available for each batch.

Communication Modules - Modbus Module

- Ability to transfer live readings, units of measure, and measurement status
- Connect to PLCs and SCADA Systems
- Supports the Serial Modbus RS485 standard

H COMM Module

- Allows communication between the 9900 Transmitter and any HART[®] enabled device
- Allows access to Primary and Secondary measurements remotely
- Allows user to remotely adjust the 4 and 20 mA settings
- Not compatible with Batch Module

Flexible solutions

Additional accessory options are available to help you with field installations. Thanks to the flexibility of the rear enclosure kits, you can install a 9900-1P on a wall, tank or pipe for indoor or outdoor use.

Rear Enclosure Kit

Hinged or Flat Cover

The rear enclosure kit allows the 9900 Transmitter to be mounted just about anywhere. The rear enclosure kit is available in two versions. The hinged cover version is suitable for wall or pipe mount installations, and allows for easy access to the back of the 9900 Transmitter for wiring and module installation. The flat cover kit is designed to fit inside a panel for waterproof protection.



Integral Mounted Systems

Integral mounted systems can be purchased directly from GF Signet or you can purchase the components to assemble the system yourself.

The 9900 field mount transmitter mounts onto the 3-8052 housing and can support any GF sensor with a rear $\frac{3}{4}$ " NPT connector such as the 2839-2842 family of Conductivity sensors, 515/8510 and 2536/8512 Flow Integral systems, 2450 Pressure and 2350 Temperature sensors.

Angle Adjustment Adapter Kit

Must be used with the Direct Conductivity/Resistivity Module 3-9900.394

The angle adjustment adapter kit quickly and easily adjusts your 9900 Integral (Field) Mount Transmitter viewing angle by 25° angle. One or more angle adapters can be installed together, which can also provide extra room for the wiring.



Benefits of field mount kits

What makes the 9900 rear enclosure so flexible, is that you can convert the panel version of the 9900 Transmitter into a field mountable transmitter. The design feature make it suitable for installations onto walls, pipes, struts or inside panels.

- Compatible with all existing 9900-1P Transmitters
- NEMA TYPE 4X/IP66 rated for indoor or outdoor installations
- Spacious for any 9900 Transmitter accessory module
- Drill holes on any side for flexible wiring orientation.



Applications

The 9900 Transmitter in a tank filling application.


The 9900 versatile parameter and modularity capabilities make the unit well suited for a variety of applications including wastewater treatment, reverse osmosis, deionization, chemical manufacturing, metal and plastic finishing, fume scrubbers, cooling towers and media filtration.



Applications

No matter which processes and applications - GF Piping Systems supports its customers in every phase of the project.

From start to finish, we stand beside our customers as a competent, reliable and experienced partner, actively contributing the know-how of an industrial company that has been successful in the market for over 200 years. With our application knowledge and product expertise we support our customers during the planning process, the sustainable realization of the projects and the provision of services.



Industrial & Municipal Water Treatment

Water treatment, whether it is for municipal or industrial applications, typically serves to improve the quality of the water to ensure public safety or to reduce negative impacts on process equipment and/or the environment. The 9900 Transmitter, part of the SmartPro family, is ideal for use in measurement and control of various water treatment applications. Industrial Water Treatment applications include media filtration, deionization, desalination, cooling tower control, reverse osmosis, and fume scrubbers, while chlorine dioxide and ozone control are common in Municipal Water Treatment applications. Monitoring the quantity and quality of various parameters such as acidity/

alkalinity of chemicals, salts, and chlorine concentrations are all important in delivering processed water to the quality standards demanded by each unique application.

Chemical Process Industry

The 9900 and applicable sensors can be used for measurement and control in the transport and dilution of various chemicals. Managing chemical tank levels and dosing of chemicals can all be monitored and controlled using the 9900 Transmitter.

Worldwide at home

Our sales companies and representatives ensure local customer support in over 100 countries.

www.gfsignet.com

Argentina / Southern South America

Georg Fischer Central Plastics
Sudamérica S.R.L.
Buenos Aires, Argentina
Phone +54 11 4512 02 90
gfcentral.ps.ar@georgfischer.com
www.gfps.com/ar

Australia

Georg Fischer Pty Ltd
Riverwood NSW 2210 Australia
Phone +61 (0) 2 9502 8000
australia.ps@georgfischer.com
www.gfps.com/au

Austria

Georg Fischer
Rohrleitungssysteme GmbH
3130 Herzogenburg
Phone +43 (0) 2782 856 43-0
austria.ps@georgfischer.com
www.gfps.com/at

Belgium / Luxembourg

Georg Fischer NV/SA
1070 Bruxelles/Brüssel
Phone +32 (0) 2 556 40 20
be.ps@georgfischer.com
www.gfps.com/be

Brazil

Georg Fischer Sist. de Tub. Ltda.
04795-100 São Paulo
Phone +55 (0) 11 5525 1311
br.ps@georgfischer.com
www.gfps.com/br

Canada

Georg Fischer Piping Systems Ltd
Mississauga, ON L5T 2B2
Phone +1 (905) 670 8005
Fax +1 (905) 670 8513
ca.ps@georgfischer.com
www.gfps.com/ca

China

Georg Fischer Piping Systems Ltd
Shanghai 201319
Phone +86 21 3899 3899
china.ps@georgfischer.com
www.gfps.com/cn

Denmark / Iceland

Georg Fischer A/S
2630 Taastrup
Phone +45 (0) 70 22 19 75
info.dk.ps@georgfischer.com
www.gfps.com/dk

Finland

Georg Fischer AB
01510 VANTAA
Phone +358 (0) 9 586 58 25
Fax +358 (0) 9 586 58 29
info.fi.ps@georgfischer.com
www.gfps.com/fi

France

Georg Fischer SAS
95932 Roissy Charles de Gaulle Cedex
Phone +33 (0) 1 41 84 68 84
fr.ps@georgfischer.com
www.gfps.com/fr

Germany

Georg Fischer GmbH
73095 Albershausen
Phone +49 (0) 7161 302-0
info.de.ps@georgfischer.com
www.gfps.com/de

India

Georg Fischer Piping Systems Ltd
400 076 Mumbai
Phone +91 224007 2001
branchoffice@georgfischer.com
www.gfps.com/in

Indonesia

Georg Fischer Pte Ltd –
Representative Office
Phone +62 21 2900 8564
Fax +62 21 2900 8566
sgp.ps@georgfischer.com
www.gfps.com/sg

Italy

Georg Fischer S.p.A.
20063 Cernusco S/N (MI)
Phone +39 02 921 861
it.ps@georgfischer.com
www.gfps.com/it

Japan

Georg Fischer Ltd
556-0011 Osaka,
Phone +81 (0) 6 6635 2691
jp.ps@georgfischer.com
www.gfps.com/jp

Korea

Georg Fischer Piping Systems
271-3 Seoheon-dong Bundang-gu
Seongnam-si, Gyeonggi-do
Seoul 463-824
Phone +82 31 8017 1450
Fax +82 31 8017 1454
kor.ps@georgfischer.com
www.gfps.com/kr

Malaysia

Georg Fischer (M) Sdn. Bhd.
No. 2, 4 & 6, Jalan Permata 3/KS 09
Taman Perindustrian Air Hitam
41200 Klang, Selangor
Phone +603 3122 5585
Fax +603 3122 5575
my.ps@georgfischer.com
www.gfps.com/my

Mexico / Northern Latin America

Georg Fischer S.A. de C.V.
Apodaca, Nuevo Leon
CP66636 Mexico
Phone +52 (81) 1340 8586
Fax +52 (81) 1522 8906
mx.ps@georgfischer.com
www.gfps.com/mx

Middle East

Georg Fischer
Piping Systems (Switzerland) Ltd
Dubai, United Arab Emirates
Phone +971 4 289 49 60
gcc.ps@georgfischer.com
www.gfps.com/int

Netherlands

Georg Fischer N.V.
8161 PA Epe
Phone +31 (0) 578 678 222
nl.ps@georgfischer.com
www.gfps.com/nl

New Zealand

Georg Fischer Ltd
13 Jupiter Grove, Upper Hutt 5018
PO Box 40399, Upper Hutt 5140
Phone +64 (0) 4 527 9813
nz.ps@georgfischer.com
www.gfps.com/nz

Norway

Georg Fischer AS
1351 Rud
Phone +47 67 18 29 00
no.ps@georgfischer.com
www.gfps.com/no

Philippines

Georg Fischer Pte Ltd
Representative Office
Phone +632 571 2365
Fax +632 571 2368
sgp.ps@georgfischer.com
www.gfps.com/sg

Poland

Georg Fischer Sp. z o.o.
05-090 Sekocin Nowy
Phone +48 (0) 22 31 31 0 50
poland.ps@georgfischer.com
www.gfps.com/pl

Romania

Georg Fischer
Piping Systems (Switzerland) Ltd
020257 Bucharest - Sector 2
Phone +40 (0) 21 230 53 80
ro.ps@georgfischer.com
www.gfps.com/int

Russia

Georg Fischer
Piping Systems (Switzerland) Ltd
Moscow 125047
Phone +7 495 258 60 80
ru.ps@georgfischer.com
www.gfps.com/ru

Singapore

George Fischer Pte Ltd
11 Tampines Street 92, #04-01/07
528 872 Singapore
Phone +65 6747 0611
Fax +65 6747 0577
sgp.ps@georgfischer.com
www.gfps.com/sg

Spain / Portugal

Georg Fischer S.A.
28046 Madrid
Phone +34 (0) 91 781 98 90
es.ps@georgfischer.com
www.gfps.com/es

Sweden

Georg Fischer AB
117 43 Stockholm
Phone +46 (0) 8 506 775 00
info.se.ps@georgfischer.com
www.gfps.com/se

Switzerland

Georg Fischer
Rohrleitungssysteme (Schweiz) AG
8201 Schaffhausen
Phone +41 (0) 52 631 30 26
ch.ps@georgfischer.com
www.gfps.com/ch

Taiwan

Georg Fischer Co., Ltd
San Chung Dist., New Taipei City
Phone +886 2 8512 2822
Fax +886 2 8512 2823
www.gfps.com/tw

United Kingdom / Ireland

Georg Fischer Sales Limited
Coventry, CV2 2ST
Phone +44 (0) 2476 535 535
uk.ps@georgfischer.com
www.gfps.com/uk

USA / Caribbean

Georg Fischer LLC
9271 Jeronimo Road
92618 Irvine, CA
Phone +1 714 731 88 00
Fax +1 714 731 62 01
us.ps@georgfischer.com
www.gfps.com/us

International

Georg Fischer
Piping Systems (Switzerland) Ltd
8201 Schaffhausen/Switzerland
Phone +41 (0) 52 631 30 03
Fax +41 (0) 52 631 28 93
info.export@georgfischer.com
www.gfps.com/int

The technical data is not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.