

Meet our VIPs

- MULTI/JOINT® 3000 Plus
- ST-System
- UNI-Coupling
- Multi/Clamp
- W400/W410




We have the solution

Connecting, repairing and tapping



MULTI/JOINT® The original!

Perfection in every detail MULTI/JOINT® 3000 Plus



RAL GÜTEZEICHEN
SCHWERER KORROSIONSSCHUTZ
VON ARMATUREN UND FORMSTÜCKEN



Certified to
NSF/ANSI 61

kiwa

WRAS
APPROVED
PRODUCT



Uni/Fiks ring

Uni/Fikser:

stainless steel
A4 (AISI 316)

Varioseal:

rubber gasket
(EPDM or NBR)

Clamp ring:

ductile cast iron
GGG45 EN
GJS-450-10
with Resicoat®
epoxy powder
coating type RT
9000 R4

Body:

ductile cast iron GGG45 EN-GJS-450-10
with Resicoat® epoxy powder coating
type RT 9000 R4

Hygiene protection:

Ensures the fitting stays
clean from production
to point of use
*(cap in the picture:
DN50 - DN400)*

Nuts:

stainless steel A2
(AISI 304) galvanised
and passivated
or stainless steel A4
(AISI 316)

Bolts:

stainless steel A2
(AISI 304) Lubo coated
or stainless steel A4
(AISI 316) Lubo coated

Washer:

stainless steel A2 (AISI 304)
or stainless steel A4 (AISI 316)



We have the solution

MULTI/JOINT® 3000 Plus

+ Maintenance & repair



+ Wide range fittings



Georg Fischer Waga N.V. develops, produces and supplies connection solutions for under and above ground water and gas applications. Our extensive product assortment is used for various purposes in transport lines, distribution networks and service lines. Whether it concerns connecting, repairing or tapping, we have the solution. With our reliable fittings we offer you quick, simple and maintenance free solutions that will last for decades.

MULTI/JOINT® 3000 Plus

- Wide range fitting suitable for all pipe materials
- Restraint and non restraint in sizes DN50 – DN600 (2" - 24")
- Working pressure up to 16 bar for water and 8 bar for gas (restraint)
- Life expectancy of at least 50 years thanks to Resicoat® epoxy powder coating

Our solutions

- Wide range fittings
- Dedicated fittings
- Repair clamps and tapping saddles
- Drilling devices

Your benefits

- Quick, safe and simple installation and repair solution
- Reduction of your stock thanks to the "one size fits and grips all" principle
- Certified product
- Reusable
- Applicable for under and above ground use



ST-System

UNI-Coupling

+ Dedicated fittings



+ Dedicated fittings



ST-System

- Tailor made solution for any pipe diameter
- Non restraint in sizes DN40 – DN2200 (1½" – 88")
- Working pressure: 10, 16 and 25 bar for water and 4 bar for gas
- Large insertion depth ensures easy installation
- Can also be used as a disassembly piece
- Life expectancy of at least 50 years thanks to Resicoat® epoxy powder coating

UNI-Coupling

- Light weight and compact stainless steel W5 fitting (Flex, Grip and Repair)
- Restraint and non restraint in sizes 21 mm – 2000 mm (1" – 80")
- Working pressure up to 70 bar
- Leak tight, patented, wedge shaped seal
- Unique grip ring with spherical profile

Your benefits

- Fully tailor made
- Quick, safe and simple installation
- Reusable
- Applicable for under and above ground use

Your benefits

- Multi purpose application
- Corrosion resistant thanks to stainless steel housing
- Quick, safe and simple installation
- Reusable
- Applicable for under and above ground use



Multi/Clamp

W400 / W410

+ Repair clamps and tapping saddles



+ Drilling devices



Multi/Clamp

- Stainless steel repair clamps in A2 (AISI 304) and A4 (AISI 316L)
- Stainless steel tapping saddles and flanges
- In sizes 15 mm – 1000 mm (½" – 40")
- Suitable for repairs under pressure
- Working pressure up to 16 bar for water and 8 bar for gas

W400 / W410

- Drilling device for drilling under pressure
- Modular drilling system with many different universal drills
- W400 for sizes ½" – 2"
- W410 for sizes 45 mm - 84 mm
- Working pressure: 16 bar for water and 8 bar for gas

Your benefits

- Corrosion resistant thanks to stainless steel housing
- Quick, safe and simple installation
- Applicable for under and above ground use

Your benefits

- One man handling on site thanks to light weight and compact design
- Designed to operate in any type of weather
- Applicable for all pipe types



Contact information

P.O. Box 290
8160 AG EPE
The Netherlands
T +31 578 678378
F +31 578 620848
www.waga.nl
waga.ps@georgfischer.com

The technical data are not binding and not expressly warranted characteristics of the goods. They are subject to change. Please consult our General Conditions of Supply.

