


Application Examples Circulation Control Valves

Installation typesDN 15 / ½" pages 2-5Installation typesDN 20 / ¾" pages 6-9Installation typeDN 25 / 1" pages 10-11

Installation types DN15 / 1/2"



<section-header>

Hycleen Automation System

Products

GF Code	Pieces	Description							
351 110 550	1	Circulation control valve 2T DN1							
350 887 710	2	Shut-off union DN15 (gasket incl							

GF Code		Pieces	Description							
	351 110 550	1	Circulation control valve 2T DN15							
	350 887 710	1	Shut-off union DN15 (gasket inclu							
	350 887 911	1	Shut-off union DN20 (gasket inclu							
	351 110 772	1	Flow sensor DN20 (insulation box							
	359 891 991	1	Double screw union in brass 1"x3/							
	350 929 423	1	Gasket ¾"							
	350 929 421	1	Gasket 1"							

Option: 1 reduction 3/4" external thread x 1/2" internal thread (on site)


5	(insulation	box	inc	lude	ed)
	ded)				

(insulation box included)
ded)
ded)
included)
n 4



4

Installation types DN15 / 1/2"






Products

GF Code	Pieces	Description							
351 110 550	1	Circulation control valve 2T DN1							
350 895 651	1	Y-type valve 5211, DN15							
350 887 710	1	Shut-off union DN15 (gasket incl							
359 891 990	1	Double screw union in brass 34">							
350 929 423	3	Gasket ¾"							
351 110 365	1	Sampling valve ¼"							
355 633 001	1	Extension to sampling valve, 35							
351 616 670	1	Insulation box DN15							

* Valves must be turned 90° or 180° against each other due to short overall length of intermediate piece




GF Code	Pieces	Description
351 110 550	1	Circulation control valve 2T DN15 (insulation box included)
350 895 651	1	Y-type valve 5211, DN15
350 887 710	1	Shut-off union DN15 (gasket included)
351 110 772	1	Flow sensor DN20 (insulation box included)
359 891 991	2	Double screw union in brass 1"x¾"
350 929 423	3	Gasket ¾"
350 929 421	2	Gasket 1"
351 110 365	1	Sampling valve ¼"
355 633 001	1	Extension to sampling valve, 35 mm, ¼"
351 616 670	1	Insulation box DN15

(insulation box included)
ıded)
3⁄4"
nm, ¼"

6

Installation types DN20 / 3/4"





Hycleen Automation System

Products

GF Code	Pieces	Description						
351 110 590	1	Circulation control valve 2T DN1						
350 887 911	2	Shut-off union DN20 (gasket incl						

GF Code	Pieces	Description
351 110 590	1	Circulation control valve 2T DN15
350 887 911	2	Shut-off union DN20 (gasket inclu
351 110 772	1	Flow sensor DN20 (insulation box
359 891 992	1	Double screw union in brass 1"x1
350 929 421	2	Gasket 1"


5	(in	۱S	u	l	a	ti	ic	1	ſ	k	D	0)	(i	n	C	:	lι	J	c	ł	e	9	d	I))
	de			••••				••••				•••	•••							• •	•••	•		••••			• •

(insulation box included)
ıded)
(included)
"



8

Installation types DN20 / 3/4"






Products

GF Code	Pieces	Description
351 110 590	1	Circulation control valve 2T DN15 (insulation box included)
350 895 652	1	Y-type valve 5211, DN20
350 887 911	1	Shut-off union DN20 (gasket included)
359 891 992	1	Double screw union in 1"x1"
350 929 421	3	Gasket 1"
351 110 365	1	Sampling valve ¼"
355 633 001	1	Extension to sampling valve, 35 mm, ¼"
351 626 670	1	Insulation box DN20

* Valves must be turned 90° or 180° against each other due to short overall length of intermediate piece



GF Code	Stk.	Description	
351 110 590	1	Circulation control valve 2T DN15 (insulation box included)	
350 895 652	1	Y-type valve 5211, DN20	
350 887 911 1 Shut-off uni		Shut-off union DN20 (gasket included)	
351 110 772	1	Flow sensor DN20 (insulation box included) Double screw union in brass 1"x1"	
359 891 992	2		
350 929 421	5	Gasket 1"	
351 110 365	1	Sampling valve ¼"	
355 633 001	1	Extension to sampling valve, 35 mm, ¼"	
351 626 670	1	Insulation box DN20	



Installation type DN25/ 1"



Hycleen Automation System

Products

GF Code	Stk.	Description
351 110 630	1	Circulation control valve 2T DN1
350 895 653	2	Y-typle valve 5211, DN25
359 891 994	2	Double screw union in brass 11/4
350 929 404	6	Gasket 1¼" (27/38x1,5)
351 110 365	1	Sampling valve ¼"
355 633 001	1	Extension to sampling valve, 35
351 632 670	2	Insulation box DN25

* Valves must be turned 90° or 180° against each other due to short overall length of intermediate piece

5 (insulation box included)						
x1¼"						
nm, ¼"						



Local support around the world

Visit our webpage to get in touch with your local specialist: **www.gfps.com/our-locations**





÷

The information and technical data (altogether "Data") herein are not binding, unless explicitly confirmed in writing. The Data neither constitutes any expressed, implied or warranted characteristics, nor guaranteed properties or a guaranteed durability. All Data is subject to modification. The General Terms and Conditions of Sale of Georg Fischer Piping Systems apply.



gfps-3778362-brochure-hasanwendungsbeispiele-en

© Georg Fischer Piping Systems Ltd CH-8201 Schaffhausen/Switzerland, 2023

÷

+ +

÷