

## Product range



**Coupling**

**Flange adaptor**

**Reduced coupling**

**Reduced flange**

## Local support around the world

Visit our webpage to get in touch  
with your local specialist:  
[www.gfps.com/our-locations](http://www.gfps.com/our-locations)



Georg Fischer Waga N.V. **+GF+**

## MULTI/JOINT® 3000 Plus New Heroes

## Technical details

| Type                   | Description       | Range 1     | Range 2     |
|------------------------|-------------------|-------------|-------------|
| Coupling               | DN900             | 899 - 931   | 899 - 931   |
| Coupling               | DN925             | 939 - 971   | 939 - 971   |
| Coupling               | DN1000            | 994 - 1026  | 994 - 1026  |
| Coupling               | DN1025            | 1042 - 1074 | 1042 - 1074 |
| Reduced Coupling       | DN925 x DN900     | 939 - 971   | 899 - 931   |
| Reduced Coupling       | DN1025 x DN1000   | 1042 - 1074 | 994 - 1026  |
| Flange adaptor         | DN900             | 899 - 931   | 900FL       |
| Flange adaptor         | DN1000            | 994 - 1026  | 1000FL      |
| Reduced flange adaptor | DN925 x DN900FL   | 939 - 971   | 900FL       |
| Reduced flange adaptor | DN1025 x DN1000FL | 1042 - 1074 | 1000FL      |

|                           |   |
|---------------------------|---|
| <b>Flange drilling</b>    | PN10/PN16                               |
| <b>Pressure</b>           | 10 bar restraint / 16 bar non restraint |
| <b>Angularity</b>         | 8 degrees per socket side               |
| <b>Gasket</b>             | EPDM or NBR                             |
| <b>Bolts/nuts/washers</b> | A4 (AISI 316)                           |



The information and technical data (altogether "Data") herein are not binding, unless explicitly confirmed in writing. The Data neither constitutes any expressed, implied or warranted characteristics, nor guaranteed properties or a guaranteed durability. All Data is subject to modification. The General Terms and Conditions of Sale of Georg Fischer Piping Systems apply.

MULTI/JOINT® 3000 Plus is available  
in dimensions DN50 - DN1025

**+GF+**

MULTI/JOINT® 3000 Plus Flyer (EN) 09.23  
© Georg Fischer Waga N.V.  
The Netherlands, 2023

# Big

## + New big dimensions

DN900, DN925, DN1000 & DN1025.

## + Wide range

Reduction of your stock costs thanks to the 'one size fits and grips all' principle.

## + Suitable for all pipe materials

AC, PE, PVC(O), GRP, (stainless) steel, (ductile) cast iron & more.

# Red

## + Resicoat® coating

Corrosion proof epoxy powder coating, Approved by GSK.

## + Ductile iron components

Durable and reliable connections for a quick, safe and simple repair solution.

# Strong

## + Full end load restraint

New dimensions suitable for water applications up to 10 bar.

## + 50 years life expectancy

Reliable and safe connections for your peace of mind.

