


Type 2850 Cond./Res. Sensor Electronics and Integral Systems with Sensor



Product description

The type 2850 Conductivity/Resistivity Sensor Electronics are available in various configurations for maximum installation flexibility. The universal mount version is for pipe, wall, or tank mounting and enables single or dual (digital versions only) inputs using any standard GF conductivity/resistivity sensor. The threaded j-box version can be used with these same GF sensors for submersible sensor mounting. It is also available as a combined integral system configuration for in-line mounting and includes a conductivity electrode in a choice of 0.01, 0.1, 1.0, 10.0 or 20.0 cm⁻¹ cell constants.

The 2850 is ideal for applications with a conductivity range of 0.055 to 400,000 µS or a resistivity range of 18.2 MΩ to 10 kΩ.

The 2850 is available with a digital (S³L) output, or a single 4 to 20 mA. The digital (S³L) output version can be paired with the 9900 or the 9950 Transmitter to extend the distance between the measuring points to 120 m (400 ft).

The 9950-10/-11 Six-Channel Transmitter allows for up to six 2850 (S³L) output conductivity sensors to be used. To optimize 9950-10/-11 I/O module selection, you can utilize 2850-63 for two conductivity sensors at a time.

The two-wire 4 to 20 mA output version is available with eight 4 to 20 mA output ranges for each electrode cell constant. Each range can be inverted and is field selectable.

EasyCal is a standard feature that automatically recognizes conductivity test solution values for simple field calibration. A certification tool is available for validation of the sensor electronics according to USP requirements.

Features

- Test certificate supplied with all 2839-2842 sensors
- Custom cell constant programmed into all integral conductivity systems at the factory
- All 2850 Sensor electronics are built with NEMA 4X / IP65 enclosures
- Integral mount systems for quick and easy installation
- Compact design for maximum installation flexibility
- Extends the distance between the measuring point and the 9900/9950's to 120 m (400 ft)
- Digital (S³L) interface or two-wire 4 to 20 mA output
- EasyCal with automatic test solution recognition
- For use with ALL GF conductivity electrodes

Applications

- Water Treatment & Water Quality Monitoring
- Reverse Osmosis
- Deionization
- Demineralizer, Regeneration & Rinse
- Scrubber, Cooling Tower and Boiler Protection
- Aquatic Animal Life Support Systems



U.S. Patent No.: 7,550,979 B2

Technical Details

General

Compatible Electrodes	All GF Conductivity Sensors
-----------------------	-----------------------------

Materials

NPT Mount Junction Box for Integral Mount	PBT
Universal/Remote Mount	PBT, PVC-C
EasyCal - Automatic Recognition of the Following Conductivity Values	146.93 μ S, 1408.8 μ S, 12856 μ S (@25 °C) (Test solutions Per ASTM D1125-95)
	10 μ S, 100 μ S, 200 μ S, 500 μ S, 1000 μ S, 5000 μ S, 10,000 μ S, 50,000 μ S, 100,000 μ S (@ 25 °C) (Standard test solutions)

Electrical

Power	12 to 24 VDC \pm 10%, regulated for 4 to 20 mA output (typically called "Loop Powered") 5 to 6.5 VDC \pm 5% regulated recommended (provided by the GF 9900, 9950, 0486), 3.0 mA max for Digital (S ³ L) output (Reverse polarity and short circuit protected)	
Digital (S ³ L) Output: Serial ASCII, TTL level 9600 bps		
Accuracy	Conductivity	\pm 2% of reading
	Temperature	< 0.2 °C
Resolution	Conductivity	0.1% of reading
	Temperature	< 0.2 °C
Update Rate	Conductivity and Temperature	< 600 ms
Available Data via Digital (S ³ L) Output	Raw conductivity Calibrated conductivity Calibrated temperature-compensated conductivity Temperature	

Max. Temperature/Pressure Rating

Operating Temperature	-10 °C to 85 °C	14 °F to 185 °F
Storage Temperature	-20 °C to 85 °C	-4 °F to 185 °F
Relative Humidity	0 to 95%, non-condensing	
Enclosure	NEMA 4X/IP65	
Current Output	Field-selectable ranges	
Factory Set Span (Integral mount only)	0.01 cell (2839, 2881)*	4 to 20 mA = 0 to 100 μ S/cm
	0.10 cell (2840, 2882)*	4 to 20 mA = 0 to 1000 μ S/cm
	1.0 cell (2841, 2883)*	4 to 20 mA = 0 to 10'000 μ S/cm
	10.0 cell (2842, 2884)*	4 to 20 mA = 0 to 200'000 μ S/cm
	20.0 cell (2823)**	4 to 20 mA = 0 to 400'000 μ S/cm
Max. Loop Resistance	50 Ω @ 12 VDC	
	325 Ω @ 18 VDC	
	600 Ω @ 24 VDC	
Accuracy	\pm 2% of output span	
Resolution	7 μ A	
Update Rate	< 600 ms	
Error Indication	22 mA	
Pure Water Compensation	When using 0.01-cm cell and raw conductivity value < 0.5 μ S, the 2850 auto-switches to compensate for non-linear temperature effects found in this low conductivity (high resistivity) range.	

* Test certificate supplied with all sensors. Custom cell constant programmed into the electronics.

** Special Order

Shipping Weight

3-2850-5X	NPT Mount Junction Box System	0.75 kg	1.75 lb
3-2850-6X	Universal Mount System	0.75 kg	1.75 lb
3-2850-5X-81	Field (Integral) Mount Systems	0.26 kg	0.57 lb
3-2850-5X-82	Field (Integral) Mount Systems	0.24 kg	0.52 lb
3-2850-5X-83	Field (Integral) Mount Systems	0.24 kg	0.53 lb
3-2850-5X-84	Field (Integral) Mount Systems	0.24 kg	0.52 lb

Standards and Approvals


CE, UKCA, FCC

RoHS compliant, China RoHS


Manufactured under ISO 9001, ISO 14001 and ISO 45001

Dimensions


2850-5X NPT Mount Junction Box Systems



2850-6X Universal Mount Systems




2850-5X-8X-1(X)(D) NEW Field (Integral) Mount Systems




Sensor	Insertion Depth
X1 (2881)	73.7 mm (2.90 in.)
X2 (2882)	35.8 mm (1.41 in.)
X3 (2883)	41.9 mm (1.65 in.)
X4 (2884)	69.9 mm (2.75 in.)

Wiring to 4 to 20 mA Loop Output








Wiring to 9900/9950 Transmitter (S³L)








*Note: Under normal operation, the shield wire does not need to be connected. However, in noisy environments, the shield should be connected to improve noise immunity.

System Overview

In-Line Installation

Panel, Wall Mount	4 to 20 mA Output	Automation System
GF Instruments - 9900 - 9950 	- Customer Supplied Programmable Logic Controller, or - Programmable Automation Controller 	- 0486 Profibus Concentrator and Customer Supplied Programmable Logic Controller or - Programmable Automation Controller 
Type 2850 Conductivity Integral System (2881-2883), or 2850 Universal Mount with any GF conductivity probe  	Fittings - Customer Supplied 3/4 in. NPT or ISO threads All sold separately	

Submersible Installation

Panel, Wall Mount	4 to 20 mA Output	Automation System
GF Instruments - 9900 - 9950 	- Customer Supplied Programmable Logic Controller, or - Programmable Automation Controller 	- 0486 Profibus Concentrator and Customer Supplied Programmable Logic Controller or - Programmable Automation Controller 
Type 2850 Universal Mount or NPT Mount Sensor Electronics with any GF conductivity probe  	Submersible Fittings - Customer Supplied 3/4 in. NPT or ISO threads All sold separately	


* The 2850 (S³L) signal can be used for distances over 30 m (100 ft). The 2850 has a limited sensor cable input length of 4.6 m (15 ft).

Note:


The 9900/9950 (with Direct Conductivity/Resistivity module) can run all conductivity sensors with 30 m (100 ft) of cable.

Application Tips


- Maximum distance between sensor and 2850 electronics is 4.6 m (15 ft).




-5X 3/4" FNPT Mount
Sensor Electronics





Integral System includes the 2850 sensor electronics and a choice of Conductivity/Resistivity electrode.



-6X Universal Mount
Sensor Electronics



Universal Sensor Electronics assembly allows sensors without the 3/4" rear thread to be used.



Field Selectable Ranges for 4 to 20 mA Operation

The chart below indicates the field selectable ranges in which the 2850 sensor electronics can be set via internal switches. All ranges can be inverted if required. Types listed below are compatible Conductivity/Resistivity electrodes.


0.01 Cell	0.10 Cell	1.0 Cell	10.0 Cell	20.0 Cell
Type 2839 / 2881	Type 2840 / 2882	Type 2841 / 2882	Type 2842 / 2884	Type 2823 (Special Order)
10 to 20 MΩ	0 to 2 μS	0 to 20 μS	0 to 200 μS	0 to 400 μS
2 to 10 MΩ	0 to 5 μS	0 to 50 μS	0 to 500 μS	0 to 1'000 μS
0 to 2 MΩ	0 to 10 μS	0 to 100 μS	0 to 1'000 μS	0 to 2'000 μS
0 to 1 MΩ	0 to 50 μS	0 to 500 μS	0 to 5'000 μS	0 to 10'000 μS
0 to 5 MΩ	0 to 100 μS	0 to 1'000 μS	0 to 10'000 μS	0 to 200'000 μS
0 to 10 MΩ	0 to 200 μS	0 to 2'000 μS	0 to 50'000 μS	0 to 100'000 μS
N/A	0 to 500 μS	0 to 5'000 μS	0 to 100'000 μS	0 to 200'000 μS
N/A	0 to 1'000 μS	0 to 10'000 μS	0 to 200'000 μS	0 to 400'000 μS

The 4 to 20 mA output ranges shown in this chart can be inverted using the internal switch Resistivity. Ranges are in BOLD

Note: The 2819-2823 series Integral Systems must be ordered through special order products.

Operating Range Chart

The 2850 is capable of measuring conductivity and resistivity values over a wide range. Below is a chart of GF Conductivity/Resistivity electrodes (listed in each range box) that is recommended for the specified measurement range.



Ordering Information

Ordering Notes

- All 2850 units can be used with any GF Conductivity/Resistivity electrode
- Integral systems are only offered with type 2839-2842 and 2881-2884 electrodes. 2818-2823 and 2870-2874 require a special order sensor.
- Dual channel units are only available in the 3-2850- 63 universal mount junction box/ remote mount configuration and with digital (S³L) output for use with the 9950-10/-11.

Mfr. Part No.	Code	Sensor	Process Threaded Connection
---------------	------	--------	-----------------------------


2850 Integral Mount Systems, (includes Sensor Electronics and 316L SS Electrode with CPVC process connection) with EasyCal

Digital (S³L) output

3-2850-51-81	159002156	2881 Electrode, 0.01 cell	NPT Threads
3-2850-51-82	159002157	2882 Electrode, 0.1 cell	NPT Threads
3-2850-51-83	159002158	2883 Electrode, 1.0 cell	NPT Threads
3-2850-51-84	159002159	2884 Electrode, 10.0 cell	NPT Threads
3-2850-51-81D	159002160	2881 Electrode, 0.01 cell	NPT Threads
3-2850-51-82D	159002161	2882 Electrode, 0.1 cell	NPT Threads
3-2850-51-83D	159002162	2883 Electrode, 1.0 cell	NPT Threads
3-2850-51-84D	159002163	2884 Electrode, 10.0 cell	NPT Threads

4 to 20 mA output

3-2850-52-81	159002164	2881 Electrode, 0.01 cell	ISO Threads
3-2850-52-82	159002165	2882 Electrode, 0.1 cell	ISO Threads
3-2850-52-83	159002166	2883 Electrode, 1.0 cell	ISO Threads
3-2850-52-84	159002167	2884 Electrode, 10.0 cell	ISO Threads
3-2850-52-81D	159002168	2881 Electrode, 0.01 cell	ISO Threads
3-2850-52-82D	159002169	2882 Electrode, 0.1 cell	ISO Threads
3-2850-52-83D	159002170	2883 Electrode, 1.0 cell	ISO Threads
3-2850-52-84D	159002171	2884 Electrode, 10.0 cell	ISO Threads



Mfr. Part No.	Code	Sensor	Process Threaded Connection
---------------	------	--------	-----------------------------


2850 Integral Mount Systems, (includes Sensor Electronics and 316L SS Electrode with Polypropylene process connection) with EasyCal

Digital (S³L) output

3-2850-51-81P	159002172	2881 Electrode, 0.01 cell	NPT Threads
3-2850-51-82P	159002173	2882 Electrode, 0.1 cell	NPT Threads
3-2850-51-83P	159002174	2883 Electrode, 1.0 cell	NPT Threads
3-2850-51-81PD	159002175	2881 Electrode, 0.01 cell	ISO Threads
3-2850-51-82PD	159002176	2882 Electrode, 0.1 cell	ISO Threads
3-2850-51-83PD	159002177	2883 Electrode, 1.0 cell	ISO Threads

4 to 20 mA output

3-2850-52-81P	159002178	2881 Electrode, 0.01 cell	NPT Threads
3-2850-52-82P	159002179	2882 Electrode, 0.1 cell	NPT Threads
3-2850-52-83P	159002180	2883 Electrode, 1.0 cell	NPT Threads
3-2850-52-81PD	159002181	2881 Electrode, 0.01 cell	ISO Threads
3-2850-52-82PD	159002182	2882 Electrode, 0.1 cell	ISO Threads
3-2850-52-83PD	159002183	2883 Electrode, 1.0 cell	ISO Threads



Mfr. Part No.	Code	Sensor	Process Threaded Connection
---------------	------	--------	-----------------------------


2850 Integral Mount Systems, (includes Sensor Electronics and 316L SS Electrode with PEEK process connection) with EasyCal

Digital (S³L) output

3-2850-51-81K	159002196	2881 Electrode, 0.01 cell	NPT Threads
3-2850-51-82K	159002197	2882 Electrode, 0.1 cell	NPT Threads
3-2850-51-83K	159002198	2883 Electrode, 1.0 cell	NPT Threads
3-2850-51-81KD	159002199	2881 Electrode, 0.01 cell	ISO Threads
3-2850-51-82KD	159002200	2882 Electrode, 0.1 cell	ISO Threads
3-2850-51-83KD	159002201	2883 Electrode, 1.0 cell	ISO Threads

4 to 20 mA output


3-2850-52-81K	159002202	2881 Electrode, 0.01 cell	NPT Threads
3-2850-52-82K	159002203	2882 Electrode, 0.1 cell	NPT Threads
3-2850-52-82K	159002204	2883 Electrode, 1.0 cell	NPT Threads
3-2850-52-81KD	159002205	2881 Electrode, 0.01 cell	ISO Threads
3-2850-52-82KD	159002206	2882 Electrode, 0.1 cell	ISO Threads
3-2850-52-82KD	159002207	2883 Electrode, 1.0 cell	ISO Threads



Note: Integral systems are shipped with a sensor and 2850 combined. Other 2850 systems are available with type 288X electrodes upon request. See individual electrode product pages for more information.

Mfr. Part No.	Code	Output
2850 Sensor Electronics with EasyCal		
NPT mount junction box (¾ inch threaded) for standpipe or integral mounting, single input only		
3-2850-51	159 001 398	One input/one digital (S ³ L) output
3-2850-52	159 001 399	One input/one 4 to 20 mA output
Universal mount junction box for remote mount, single or dual input*		
3-2850-61	159 001 400	One input/one digital (S ³ L) output for use with 9900 or 9950
3-2850-62	159 001 401	One input/one 4 to 20 mA output
3-2850-63	159 001 402	Dual digital (S ³ L) outputs

*For use when remote sensor mounting is desired. Compatible with ALL GF conductivity electrodes. See individual electrode product pages for more information.



Accessories and Replacement Parts

Mfr. Part	Code	Description
3-2850.101-1	159 001 392	Plug-in NIST Traceable Recertification Tool, 1.0 µS simulated
3-2850.101-2	159 001 393	Plug-in NIST Traceable Recertification Tool, 2.5 µS simulated
3-2850.101-3	159 001 394	Plug-in NIST Traceable Recertification Tool, 10.0 µS simulated
3-2850.101-4	159 001 395	Plug-in NIST Traceable Recertification Tool, 18.2 MΩ simulated
3-2850.101-5	159 001 396	Plug-in NIST Traceable Recertification Tool, 10.0 MΩ simulated
5523-0322V	159 001 807	**Sensor cable (per ft), 3 cond. plus shield, 22 AWG

** Although a customer can extend the cable of a conductivity sensor, GF does not recommend this, and offers extended cable lengths from the factory.

The information and technical data (altogether "Data") herein are not binding, unless explicitly confirmed in writing. The Data neither constitutes any expressed, implied or warranted characteristics, nor guaranteed properties or a guaranteed durability. All Data is subject to modification. The General Terms and Conditions of Sale of Georg Fischer Piping Systems apply.

3-2850-3.099 Rev F

11/2024-A

© Georg Fischer Piping Systems Ltd, 8201 Schaffhausen/Switzerland

Tel. +41 52 631 11 11 • www.gfps.com • E-Mail: info.ps@georgfischer.com