

MULTI/JOINT® 3000 Plus

MULTI/JOINT® type 3000 & 3007 Plus coupling



size (DN)	range (mm)	size (DN)	range (mm)
50	46-71	475	481-513
65	63-90	500	500-532
80	84-105	550	548-580
100	104-132	600	605-637
125	132-155	625	630-662
150	154-192	675	665-697
200	192-232	700	709-741
225	230-268	750	745-777
250	267-310	800	799-831
300	315-356	825	837-869
350	352-393	900	899-931
400	392-433	925	939-971
425	432-464	1000	994-1026
450	450-482	1025	1042-1074

MULTI/JOINT® type 3050 & 3057 Plus flange adaptor



size (DN)	range (mm)	flange (DN)	size (DN)	range (mm)	flange (DN)
50	46-71	50	350	352-393	350
65	63-90	60/65	400	392-433	400
80	84-105	80	450	450-482	450
100	104-132	100	500	500-532	500
125	132-155	125	600	605-637	600
150	154-192	150	700	709-741	700
200	192-232	200	800	799-831	800
250	267-310	250	900	899-931	900
300	315-356	300	1000	994-1026	1000

MULTI/JOINT® type 3150 & 3157 Plus reduced flange adaptor



size (DN-FL)	range (mm)	flange (DN)
50-40	46-71	40
65-80	63-90	80
100-80	104-132	80
125-100	132-155	100
125-150	132-155	150
150-100	154-192	100
200-150	192-232	150
225-200	230-268	200
225-250	230-268	250
300-250	315-356	250
350-300	352-393	300
425-400	432-464	400
450-400	450-482	400
475-400	481-513	400
550-500	548-580	500
625-600	630-662	600
675-600	665-697	600
825-800	837-869	800
925-900	939-971	900
1025-1000	1042-1074	1000

MULTI/JOINT® type 3100 & 3107 Plus reduced coupling



size (DN-DN)	range (mm)	range (mm)
50-65	46-71	63-90
65-80	63-90	84-105
80-100	84-105	104-132
100-125	104-132	132-155
100-150	104-132	154-192
125-150	132-155	154-192
150-200	154-192	192-232
200-225	192-232	230-268
200-250	192-232	267-310
225-250	230-268	267-310
250-300	267-310	315-356
300-350	315-356	352-393
300-400	315-356	392-433
350-400	352-393	392-433
400-425	392-433	432-464
400-450	392-433	450-482
425-475	432-464	481-513
450-500	450-482	500-532
500-550	500-532	548-580
550-600	548-580	605-637
600-625	605-637	630-662
600-675	605-637	665-697
600-700	605-637	709-741
750-800	745-777	799-831
800-825	799-831	837-869
900-925	899-931	939-971
1000-1025	994-1026	1042-1074

MULTI/JOINT® type 3067 Plus PE adaptor



size (DN)	range (mm)	PE outlet (mm)
50	46-71	50
50	46-71	63
65	63-90	63
65	63-90	75
80	84-105	90
80	84-105	110
100	104-132	90
100	104-132	110
100	104-132	125
125	132-155	110
125	132-155	125
125	132-155	140
125	132-155	160
150	154-192	160
150	154-192	180
200	192-232	200
200	192-232	225
225	230-268	250
250	267-310	250
250	267-310	280
300	315-356	315

MULTI/JOINT® type 3400 & 3407 Plus bend



size (DN)	range (mm)
80	84-105
100	104-132
150	154-192

MULTI/JOINT® type 3207 Plus end cap blind



size (DN)	range (mm)
50	46-71
65	63-90
80	84-105
100	104-132
125	132-155
150	154-192
200	192-232
225	230-268
250	267-310
300	315-356
400	392-433

MULTI/JOINT® type 3207 Plus end cap threaded



size (DN)	range (mm)	thread (inch)
50	46-71	¾" - 2"
65	63-90	¾" - 2"
80	84-105	¾" - 2"
100	104-132	¾" - 2"
125	132-155	¾" - 2"
150	154-192	¾" - 2"
200	192-232	¾" - 2"
225	230-268	¾" - 2"
250	267-310	¾" - 2"
300	315-356	¾" - 2"
400	392-433	¾" - 2"

MULTI/JOINT® type 3557 Plus reduced duckfoot (2 inch outlet)



size (DN-FL)	range (mm)	flange (DN)
65-80	63-90	80
100-80	104-132	80
125-80	132-155	80
150-80	154-192	80

