GF Piping Systems

CONTAIN-IT Plus Systems

Questionnaire for Static Evidence and Stress Calculation DVS 2210-2

General project information

Project name	
Customer	
CRM/Order number	

Flow media

Flow media		%
Density (in g/cm³)		
MSDS (Material Safety Data Sheet) attached?	☐ Yes	☐ No

Operation conditions

			Total load time	
Maximum working temperature		°C	in percent	%
Minimum working temperature		°C	in percent	%
Maximum working pressure		bar	in percent	%
Minimum working pressure		bar	in percent	%
Period w/o media/empty			in percent	%
Ambient temperature	Minimum	°C	Maximum	°C
Required service life	☐ 10 years	☐ 25 years		

Parameter pipes

	Inner pipe	Outer pipe	
Material		☐ PE-100	☐ PVC-U (transparent)
Outer diameter d			
Wall thickness e			
Nominal pressure PN			
Standard dimension ratio (SDR)			
Expected connection technology			

Installation details

	Installation detail 1		Installation detail 2	
Additional system data	☐ Above the ground	☐ In the ground (buried)	☐ In building	☐ Outdoor
	Longest straight pipe run >10m?		☐ Yes	☐ No
	Heat tracing?		☐ Yes	☐ No
	Insulation thickness			mm
Installation temperature	Minimum	°C	Maximum	°C

Leak detection information

Leak detection information	☐ Optical	☐ Sensor	☐ Detection cable	
	☐ Overpressure difference		[mbar]	☐ No pressure
	☐ Underpressure			

Comments	
Attachements	☐ Isometric drawing ☐ ☐

Your contact
Georg Fischer Piping Systems Ltd.
Ebnatstrasse 111, 8201 Schaffhausen / Switzerland
gss@georgfischer.com / www.gfps.com

GFDO_OP_00037b_EN (03.21)